1310 Optical Power Amplifier

Overview

The Optilab SOA-1310-BP is a semiconductor optical amplifier with high fiber-to-fiber gain, designed to be used in general applications to increase optical launch power to compensate for loss of other optical devices, or as a broadband ASE source. For increased utility, the SOA-1310-BP can be. Test conditions: CW operation, 2000mA, chip temperature 25°C, input signal 10dBm, the case mounted on room temperature heatsink. 6, 122 (2000)] ** Measured in 1nm span around spectrum maximum with 20pm resolution. *** For PM fiber. Customized 1310 nm Booster Optical Amplifiers (BOA) engineered for your needs. High stability, wavelength precision, and full in-house production ensure top performance and flexibility across all diode types. Two configurations are available: Polarization Maintaining (PM) fiber or Single Mode (SM) fiber input/output. It has two package configuration choices.

Article Content

Semiconductor Optical Amplifier, 1310nm, Rackmount – Optilab

The Optilab SOA is a semiconductor optical amplifier with high fiber-to-fiber gain, designed to be used in general applications to increase optical launch power to compensate for loss of other optical devices.

1310 nm Semiconductor Optical Amplifier, Butterfly Package

The Optilab SOA-1310-BPis a semiconductor optical amplifier with high fiber-to-fiber gain, designed to be used in general applications to increase optical launch power to compensate for loss of other

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Optical amplifier at 1310nm

Semiconductor Optical Amplifier at 915nm, 980nm, 1060nm, 1310nm, and 1550nm in 14-pin butterfly package

1310 nm Booster Optical Amplifiers (BOA)| Innolume

Customized 1310 nm Booster Optical Amplifiers (BOA) engineered for your needs. High stability, wavelength precision, and full in-house production ensure top performance and flexibility across all

Fiber Optical Amplifier 1250-1350nm O-Band (up to 16dBm)

The SOAA provides cost-effective solutions for 1310nm O-band optical amplification. It is a semiconductor with a fiber-coupled waveguide structure. Two configurations are available:

Customized 1310nm Semiconductor Optical Amplifier (SOA)

SOA (Semiconductor Optical Amplifier), implemented between the 1310nm multiplexer port and the LR4 transceiver, are amplifying the 1310nm spectrum. It can be used in the10G/100G system, suitable for

Custom Semiconductor Optical Amplifier (SOA), 1310nm

SOA amplifier is designed for signal amplification with 1310 wavelength. Wide bandwidth, low noise figure, and unique AGC or APC mode to ensure the high stability and reliability of output power.

Datasheet

The SOAA provides cost-effective solutions for 1310nm O-band optical amplification. It is a semiconductor with a fiber-coupled waveguide structure. Two configurations are available:

Customized 1310nm Semiconductor Optical Amplifier (SOA)

Description Semiconductor optical amplifier (SOA) uses the semiconductor as the gain medium, which are designed to be used in general applications to increase optical launch power to compensate for

Customized 1310nm Semiconductor Optical Amplifier (SOA)

1310nm Semiconductor Optical Amplifier Design of SOA optical fiber amplifier for signal amplification with 1310 wavelength band, the transparent transmission protocol, suitable for high speed signal

Customized 1310nm Semiconductor Optical Amplifier (SOA)

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

1310nm Semiconductor Optical Amplifier The SOA is a comprehensive module integrating a pump optical laser and either AGC (automatic gain control) or APC (automatic power control) circuits. It is

Performance comparison of the 1310nm optical amplifiers

One of the key optical transmission components are optical amplifiers. In this paper studies on the amplification properties of the 1310 nm optical amplifiers are presented. The evaluated

Booster Optical Amplifiers (BOA)

Booster Optical Amplifiers (BOAs) from Innolume provide over 400 mW (fiber-coupled) and up to 550 mW (submount) output power with small signal gain exceeding 40 dB. Featuring tilted waveguides

1310 nm Raman amplifier utilizing high-power, quantum-dot pumping ...

Progress in the high power quantum dot lasers allows realization of the 1310 nm Raman amplifier with the gain over 15-18 dB and very low noise figure [3, 12].

QSOA-1310

The QSOA-1310 from QPhotonics is a Optical Amplifier with Noise Figure 6 dB, Saturated Output Power 10 dBm, Saturated Output Power 10 dBm, Gain 15 to 25

Experimental performance of semiconductor optical amplifiers and ...

One of the key optical transmission components is optical amplifiers. Studies on the amplification properties of the 1310-nm optical amplifiers are presented. The evaluated optical

BOA1310P

The BOA1310P from Thorlabs Inc is a Optical Amplifier with Noise Figure 7 to 9 dB, Saturated Output Power 20 to 20.5 dBm, Saturated Output Power 20 to 20.5 dBm, Gain 28.5 to 32 dB, Operating

1310 nm Raman amplifier utilizing high-power, quantum-dot pumping ...

Abstract The Raman amplifier can be used to increase the range of 1310 nm transmission. In the paper, we present detailed studies regarding the design and performance of the 1310 nm

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Contact Us

Continue your research online:

Website: https://cjcconsultants.co.za
Technical inquiry: https://cjcconsultants.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved