
Fiber Optic Red Light Source Event Blind Zone 1m Configuration Scheme



Overview

When testing an optical fiber link, at least one blind spot will be created, which is the connection point between the OTDR and the optical fiber. The dead zone is a major shortcoming...

Key Takeaways

A 1mW red light Visual Fault Locator (VFL) can detect fiber breaks and bends, with a 1-meter event blind zone where faults cannot be immediately observed.

How It Works

A Visual Fault Locator (VFL) emits a 650nm red laser through the fiber optic cable. When the light encounters a break, bend, or poor connection, it scatters or leaks out, making the fault visible along the fiber length.

The VF

L can operate in continuous wave (CW) or pulsed mode, allowing technicians to trace fibers, identify breaks, and check continuity efficiently.

Event Blind Zone

The event blind zone refers to the minimum distance from the VFL input where a fault can be detected. A 1-meter blind zone means that any fault occurring within 1 meter of the fiber input may not be immediately visible, as the light has not yet sufficiently scattered to be detected. This is important for short fiber runs or near-end faults, where additional testing methods may be required.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Compatibility and Usage

Compatible with SC, ST, FC, and E2000 connectors; LC and MU connectors may require adapters. Suitable for single-mode and multi-mode fibers, with a typical detection range of 3–5 km. Ideal for field inspections, fiber tracing, and troubleshooting OTDR dead zones, where conventional OTDRs may not detect near-end faults.

Compact, pen-style devices are lightweight and durable, making them convenient for on-site maintenance.

Practical Considerations

Avoid looking directly into the laser to prevent eye injury. Clean fiber connectors before testing to ensure accurate fault detection. The 1-meter blind zone should be considered when testing very short fiber segments or near patch panels.

In summary, a 1mW red light VFL with a 1-meter blind zone is a reliable tool for detecting fiber faults, but technicians should be aware of the blind zone limitation and use complementary methods for near-end fault detection.

Article Content

OTDR Blind Area Analysis

When testing an optical fiber link, at least one blind spot will be created, which is the connection point between the OTDR and the optical fiber. The dead zone is a major shortcoming...

Contact Us

Continue your research online:

Website: https://cjcconsultants.co.za
Technical inquiry: https://cjcconsultants.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved