Greek Double Ladder Side Cable Tray Specifications



Overview

All rung to side member connections shall have both a mechanical and a chemical (adhesive) lock. The tray shall be assembled by the use of a locking pin made of fiberglass reinforced thermoplastic.

Key Takeaways

The Greek Double Ladder Side Cable Tray is a ladder-type system designed for heavy-duty cable support, typically made from fiberglass or steel, with defined rung spacing, side rails, and compliance with IEC 61537 and ASTM standards.

Material and Construction

Fiberglass Option: Pultruded, compression molded, or resin transfer molded fiberglass reinforced plastic (FRP) with 45–65% glass fiber content in pultruded components and 25–45% in molded components.

U

V inhibitors and fire retardant additives ensure Class 1 flame spread rating (≤25 per ASTM E-84) and chemical resistance. Conductive resin systems may include carbon additives for static dissipation. Metallic Option: Hot-dip galvanized or bare steel, with epoxy or powder coatings for corrosion protection.

Steel trays are typically MIG welded or mechanically fastened.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Dimensions and Load Capacity

Nominal Depths: 2” (51 mm), 3” (76 mm), 5” (127 mm), 7” (178 mm), 9” (229 mm) depending on cable volume and load requirements. Rung Spacing: Standard spacing varies, often 300–500 mm center-to-center, providing support for horizontal and vertical cable runs. Side Rails: Two longitudinal members forming the ladder sides, connected by transverse rungs.

Side rails provide structural rigidity and support for cable loads. Safe Working Load (SWL): Determined per IEC 61537, with load vs. span tables provided by the manufacturer. Maximum deflection is measured at mid-span for single-span installations.

Compliance and Standards

International Standards: IEC 61537 for cable tray systems, ASTM E-84 for fire performance, and ABS rules for conductive FRP trays on marine or offshore installations.

C

E Marking: Metallic trays may comply with European directives and national standards, verified by third-party certification (e.g., UL, IMQ, LCIE),. Corrosion Protection: FRP trays resist chemical and UV degradation; metallic trays use galvanization or coatings for long-term durability.

Installation Considerations

Support System: Must withstand cable load; anchor type and spacing depend on tray material and span length. Cable Management: Rungs allow secure cable tie-downs; cables can enter or exit from top or bottom. Vertical and horizontal runs are supported with minimal sag.

Thermal Expansion: Metallic trays require allowances for expansion and contraction; FRP trays have lower thermal conductivity but may require expansion joints in long runs.

Accessories and Fittings

Fittings: Elbows, tees, reducers, vertical risers, and covers are available to match straight tray sections. Covers: Optional for protection against dust, moisture, or mechanical damage. Joint Connectors: Ensure structural continuity and maintain electrical grounding where required.

Summary

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

The Greek Double Ladder Side Cable Tray is a versatile, durable system suitable for industrial, commercial, and offshore applications. It offers high load capacity, corrosion resistance, fire retardancy, and compliance with international standards, with options in fiberglass or steel to meet environmental and mechanical requirements. Proper design, support, and installation ensure reliable cable management and long-term performance.

Article Content

Enduro_Specification_Ladder Cable Tray_04-30-21

All rung to side member connections shall have both a mechanical and a chemical (adhesive) lock. The tray shall be assembled by the use of a locking pin made of fiberglass reinforced thermoplastic. The

CABLE TRAY, CABLE LADDER, CABLE TRUNKING CATALOGUE

Height (H): 50mm, 70mm, 100mm, 120mm, 150mm. Depth (D): 1.2mm, 1.5mm, 2.0mm. / Hot dip galvani CABLE TRAY Straight Section.

Niedax Catalog for cable support systems

The new continuous side rail perforation enables the wall connection parts to be screwed in without steps or drilling, and the cable ladder is flexible in use and can be used for both vertical and

CABLE LAddEr TrAY

It is important to note that the Cable Ladder Tray will come under its greatest stress when cables are being pulled into the tray. Therefore, proper placement of supports is necessary to ensure that the

Cable Tray System Specifications Guide

It describes the various components, including standard lengths, widths, heights, materials, and technical specifications. Load ratings and cable tray selection guidelines are presented based on

GUIDE CABLE TRAYS TECHNICAL

NEMA VE 1-2017 Specifies requirements for metal cable trays and associated fittings designed for use in accordance with the rules of Canadian Electrical Code, Part I and the National Electrical Code®

GRP Cable trays and ladders, connections, related accessories and ...

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Technical specifications of GRP cable trays The materials used to produce this product are polyester resin, vinylester resin or phenolic resin. Cable trays can be made with a length of up to 3 meters and

Best Practice Guide to Cable Ladder and Cable Tray Systems

These guidelines will be particularly useful for the design, specification, procurement, installation and maintenance of these systems. Cable ladder systems and cable tray systems are designed for use

Cable Tray Technical Guide A practical guide to product selection and ...

In designing supports for a cable tray system, consideration should be given to the loads associated with future cable additions and any additional loading that may be applied to the cable tray system (e.g.,

GUIDE CABLE TRAYS TECHNICAL

In accordance with its continuous impro-vement policy, Legrand reserves the right to change the specifications and illus-trations without notice. All illustrations, descriptions and technical information

Enduro_Specification_Ladder Cable Tray_04-30-21

Straight section ladder tray shall be prefabricated structures made from fiberglass reinforced plastic, consisting of two longitudinal members (side rails) connected by transverse rungs, meeting all the

Best practice guide to cable ladder and cable tray systems

Cable ladder and cable tray systems The following recommendations are intended to be a practical guide to ensure the safe and proper installation of cable ladder and cable tray systems

KwikRail cable tray specification Document

Ladder Cable Trays shall consist of two longitudinal members (side rails) with transverse members (rungs) either mechanically fastened or welded to the side rails with the option to add mechanically

Cable Tray and Ladder | PDF

The document contains specifications for cable ladder and tray systems including dimensions, materials, and part numbers. It lists various component types such as straight cable ladders, accessories, and

Aluminum Cable Ladder Specifications | PDF | Screw | Length

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

The document discusses aluminum cable ladder products from series 2, 3, 4, and 5. It provides information on straight sections, accessories, fittings, and fitting covers. Specifications are given for

TECHNICAL AND SIZING DATA

TECHNICAL DATA UNITRAY LADDER TRAY is a structure consisting of two longitudinal side members connected by individual transverse members (rungs). Rungs are welded to the side members by

Cable Ladder Trays (Welded and Swaged)

Cable Ladder Trays (Welded & Swaged) Cable Ladder Trays, are designed to meet most requirements of cable and electrical wire installations and comply to local

Cable Tray

Cable Ladders Straight sections of ladder type cable trays consist of two longitudinal side rails, connected by individual transverse members, or rungs, which are welded to the side rails or bolted in

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://cjcconsultants.co.za
Technical inquiry: https://cjcconsultants.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved